

## 6.2 ZÁSUVKOVÉ SKŘÍŇE A STAVENIŠTNÍ ROZVÁDĚČE V KRYTÍ IP54 - IP65

### 6.2 WIRED ENCLOSURES WITH IP65 SOCKETS



1

Obj. č.	Zásuvky	Chránič	Jističe
<b>v125</b>	3x 230 V / 16 A / 3p	Pouze vydrátovaná	
<b>v130</b>	3x 230 V / 16 A / 3p	-	3x PL7 B16/1
<b>v130-6kA</b>	3x 230 V / 16 A / 3p	-	3x PL6 B16/1
<b>v134</b>	3x 230 V / 16 A / 3p	1x PF7 25/2/003	3x PL7 B16/1
<b>v134-6kA</b>	3x 230 V / 16 A / 3p	1x PF6 25/2/003	3x PL6 B16/1
<b>v135</b>	3x 230 V / 16 A / 3p	1x PF7 40/4/003	3x PL7 B16/1
<b>v135-6kA</b>	3x 230 V / 16 A / 3p	1x PF6 40/4/003	3x PL6 B16/1



Rozměry (mm)	
Výška	245
Šířka	215
Hloubka	155

Použité pouzdro: 3957

Počet modulů: 9

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



2



3

TOP

Obj. č.	Zásuvky	Chránič	Jističe
<b>v272</b>	3x 230 V / 16 A / 3p	Pouze vydrátovaná	
<b>v275</b>	3x 230 V / 16 A / 3p	-	3x PL7 B16/1
<b>v275-6kA</b>	3x 230 V / 16 A / 3p	-	3x PL6 B16/1
<b>v279</b>	3x 230 V / 16 A / 3p	1x PF7 25/2/003	3x PL7 B16/1
<b>v279-6kA</b>	3x 230 V / 16 A / 3p	1x PF6 25/2/003	3x PL6 B16/1



Rozměry (mm)	
Výška	490
Šířka	125
Hloubka	107

Použité pouzdro: 3950

Počet modulů: 6

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



4



5

Obj. č.	Zásuvky	Chránič	Jističe
<b>v145</b>	4x 230 V / 16 A / 3p	1x PF7 40/4/003	4x PL7 B16/1
<b>v145-6kA</b>	4x 230 V / 16 A / 3p	1x PF6 40/4/003	4x PL6 B16/1



Rozměry (mm)	
Výška	245
Šířka	215
Hloubka	155

Použité pouzdro: 3957

Počet modulů: 9

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



6



7

Obj. č.	Zásuvky	Chránič	Jističe
<b>v281</b>	4x 230 V / 16 A / 3p	Pouze vydrátovaná	
<b>v283</b>	4x 230 V / 16 A / 3p	-	2x PL7 B16/1
<b>v283-6kA</b>	4x 230 V / 16 A / 3p	-	2x PL6 B16/1
<b>v285</b>	4x 230 V / 16 A / 3p	-	4x PL7 B16/1
<b>v285-6kA</b>	4x 230 V / 16 A / 3p	-	4x PL6 B16/1
<b>v287</b>	4x 230 V / 16 A / 3p	1x PF7 25/2/003	2x PL7 B16/1
<b>v287-6kA</b>	4x 230 V / 16 A / 3p	1x PF6 25/2/003	2x PL6 B16/1
<b>v288</b>	4x 230 V / 16 A / 3p	1x PF7 25/2/003	4x PL7 B16/1
<b>v288-6kA</b>	4x 230 V / 16 A / 3p	1x PF6 25/2/003	4x PL6 B16/1



Rozměry (mm)	
Výška	490
Šířka	125
Hloubka	107

Použité pouzdro: 3950

Počet modulů: 6

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



8



9



10