

Zásuvkové skříně v pouzdře AcquaCOMBI | AcquaCOMBI Cabled industrial boxes

Obj.č.	Zásuvky	Chránič	Jističe
v262	2x 400V / 16A / 5p 2x 230V / 16A / 3p	Pouze vydrátovaná	
vf264	2x 400V / 16A / 5p 2x 230V / 16A / 3p	-	1x KBS3B16 B16/3 2x KBS1B16 B16/1
v264	2x 400V / 16A / 5p 2x 230V / 16A / 3p	-	1x PL7 B16/3 2x PL7 B16/1
vf264-6kA	2x 400V / 16A / 5p 2x 230V / 16A / 3p	-	1x KBF3B16 B16/3 2x KBF1B16 B16/1
v264-6kA	2x 400V / 16A / 5p 2x 230V / 16A / 3p	-	1x PL6 B16/3 2x PL6 B16/1



Obj. č. / Item **v264-6kA**



Rozměr pouzdra	
Výška	490
Šířka	125
Hloubka	107
Použité pouzdro: 3950	
Počet modulů: 6	
Stupeň krytí: IP54	
Normy: EN 62208, IEC 61439-3	

Obj.č.	Zásuvky	Chránič	Jističe
vf599	2x 400V / 16A / 5p 2x 230V / 16A / 3p	1x AUR8463A030 63/4/003-A	2x KBS3B16 B16/3 2x KBS1B16 B16/1
v599	2x 400V / 16A / 5p 2x 230V / 16A / 3p	1x PF7 40/4/003-A	2x PL7 B16/3 2x PL7 B16/1
vf599-6kA	2x 400V / 16A / 5p 2x 230V / 16A / 3p	1x AUR8463A030 63/4/003-A	2x KBF3B16 B16/3 2x KBF1B16 B16/1
v599-6kA	2x 400V / 16A / 5p 2x 230V / 16A / 3p	1x PF6 40/4/003-A	2x PL6 B16/3 2x PL6 B16/1



Obj. č. / Item **v599**



Rozměr pouzdra	
Výška	330
Šířka	330
Hloubka	155
Použité pouzdro: 3974	
Počet modulů: 16	
Stupeň krytí: IP54	
Normy: EN 62208, IEC 61439-3	

Obj.č.	Zásuvky	Chránič	Jističe
v512	2x 400V / 16A / 5p 3x 230V / 16A / 3p	Pouze vydrátovaná	
vf515	2x 400V / 16A / 5p 3x 230V / 16A / 3p	-	2x KBS3B16 B16/3 2x KBS1B16 B16/1
v515	2x 400V / 16A / 5p 3x 230V / 16A / 3p	-	2x PL7 B16/3 2x PL7 B16/1
vf515-6kA	2x 400V / 16A / 5p 3x 230V / 16A / 3p	-	2x KBF3B16 B16/3 2x KBF1B16 B16/1
v515-6kA	2x 400V / 16A / 5p 3x 230V / 16A / 3p	-	2x PL6 B16/3 2x PL6 B16/1
vf516	2x 400V / 16A / 5p 3x 230V / 16A / 3p	-	2x KBS3B16 B16/3 3x KBS1B16 B16/1
v516	2x 400V / 16A / 5p 3x 230V / 16A / 3p	-	2x PL7 B16/3 3x PL7 B16/1
vf516-6kA	2x 400V / 16A / 5p 3x 230V / 16A / 3p	-	2x KBF3B16 B16/3 3x KBF1B16 B16/1
v516-6kA	2x 400V / 16A / 5p 3x 230V / 16A / 3p	-	2x PL6 B16/3 3x PL6 B16/1
TOP vf520	2x 400V / 16A / 5p 3x 230V / 16A / 3p	1x AUR8463A030 63/4/003-A	1x KBS3B16 B16/3 2x KBS1B16 B16/1
TOP v520	2x 400V / 16A / 5p 3x 230V / 16A / 3p	1x PF7 40/4/003-A	1x PL7 B16/3 2x PL7 B16/1
vf520-6kA	2x 400V / 16A / 5p 3x 230V / 16A / 3p	1x AUR8463A030 63/4/003-A	1x KBF3B16 B16/3 2x KBF1B16 B16/1
v520-6kA	2x 400V / 16A / 5p 3x 230V / 16A / 3p	1x PF6 40/4/003-A	1x PL6 B16/3 2x PL6 B16/1



Obj. č. / Item **v520**



Rozměr pouzdra	
Výška	330
Šířka	215
Hloubka	155
Použité pouzdro: 3958	
Počet modulů: 9	
Stupeň krytí: IP54	
Normy: EN 62208, IEC 61439-3	

Obj.č.	Zásuvky	Chránič	Jističe
v1117	2x 400V / 16A / 5p 4x 230V / 16A / 3p	Pouze vydrátovaná	
vf1118	2x 400V / 16A / 5p 2x 230V / 16A / 3p	-	1x KBS3B16 B16/3 2x KBS1B16 B16/1
v1118	2x 400V / 16A / 5p 4x 230V / 16A / 3p	-	1x PL7 B16/3 2x PL7 B16/1
v1118-6kA	2x 400V / 16A / 5p 4x 230V / 16A / 3p	-	1x KBF3B16 B16/3 2x KBF1B16 B16/1
v1118-6kA	2x 400V / 16A / 5p 4x 230V / 16A / 3p	-	1x PL6 B16/3 2x PL6 B16/1
vf1119	2x 400V / 16A / 5p 4x 230V / 16A / 3p	-	1x KBS3B16 B16/3 4x KBS1B16 B16/1
v1119	2x 400V / 16A / 5p 4x 230V / 16A / 3p	-	1x PL7 B16/3 4x PL7 B16/1
vf1119-6kA	2x 400V / 16A / 5p 4x 230V / 16A / 3p	-	1x KBF3B16 B16/3 4x KBF1B16 B16/1
v1119-6kA	2x 400V / 16A / 5p 4x 230V / 16A / 3p	-	1x PL6 B16/3 4x PL6 B16/1
vf1120	2x 400V / 16A / 5p 4x 230V / 16A / 3p	-	2x KBS3B16 B16/3 2x KBS1B16 B16/1
v1120	2x 400V / 16A / 5p 4x 230V / 16A / 3p	-	2x PL7 B16/3 2x PL7 B16/1
vf1120-6kA	2x 400V / 16A / 5p 4x 230V / 16A / 3p	-	2x KBF3B16 B16/3 2x KBF1B16 B16/1
v1120-6kA	2x 400V / 16A / 5p 4x 230V / 16A / 3p	-	2x PL6 B16/3 2x PL6 B16/1
vf1122	2x 400V / 16A / 5p 4x 230V / 16A / 3p	1x AUR8463A030 63/4/003-A	1x KBS3B16 B16/3 2x KBS1B16 B16/1
v1122	2x 400V / 16A / 5p 4x 230V / 16A / 3p	1x PF7 40/4/003-A	1x PL7 B16/3 2x PL7 B16/1
vf1122-6kA	2x 400V / 16A / 5p 4x 230V / 16A / 3p	1x AUR8463A030 63/4/003-A	1x KBF3B16 B16/3 2x KBF1B16 B16/1
v1122-6kA	2x 400V / 16A / 5p 4x 230V / 16A / 3p	1x PF6 40/4/003-A	1x PL6 B16/3 2x PL6 B16/1



Obj. č. / Item **v1122**



Rozměr pouzdra	
Výška	330
Šířka	215
Hloubka	155
Použité pouzdro: 3958	
Počet modulů: 9	
Stupeň krytí: IP54	
Normy: EN 62208, IEC 61439-3	